## ThinkCentre M630e Tiny 10YM00AHAC

Product

ThinkCentre M630e Tiny

Region LA

Country/Region Argentina

Machine Type 10YM

TopSeller No

Processor Intel Pentium Gold 5405U (2C / 4T, 2.3GHz, 2MB)

Chipset Intel SoC Platform

Graphics Integrated Intel UHD Graphics 610

Memory 1x 4GB DDR4-2666

Storage 1x 128GB SSD M.2 2242 PCIe 3.0x2 NVMe

Optical None

Speaker 1.5Wx1

Ethernet Integrated 100/1000M

WLAN + Bluetooth Intel 3165 11ac. 1x1 + BT4.2

**Optional Rear Ports** None

**Chassis Intrusion Switch Chassis Intrusion Switch** 

Kensington Cable Lock None

Adapter Cage None

**Toolless Chassis Screw** None

Dust Filter None

VESA Mount None

Color Black

Stand

None

Kevboard

USB Calliope Keyboard, Black, Spanish (LA)

#### Mouse

**USB** Calliope Mouse

Power Supply 65W 88% Adapter

Additional Certificates None

Monitor Cable None

System Management None

**Operating System** None

**Bundled Software** None

Base Warrantv 1-year, Onsite

**Bundled Service** None

EAN/UPC/JAN 195235922576

End of Support N/A

Announce Date 2020-08-04

#### **Recommended Services**

#### Best

5Y Premier Support Upgrade from 1Y Onsite (5WS0T36190) Better

4Y Premier Support Upgrade from 1Y Onsite (5WS0T36168)

#### Good

3Y Premier Support Upgrade from 1Y Onsite (5WS0T36147)

## WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.

### https://psref.lenovo.com

# PSREF

Visit psref website for the latest version of Product specifications Reference. © Lenovo, 2020. All rights reserved.



## ThinkCentre M630e Tiny Platform Specifications

Product Specifications Reference (PSREF)

Image: solution of the second state in the second state is the	Processor	Intel <sup>®</sup> Pentium <sup>®</sup> , or 8th Generation Intel Core™ i3 / i5 Processor						Security chip	None			
Image: Performance of the state o		Processor			Cache			Security features				
Loss During Concerner         Link Source         Stratu Strate         Strate         Stratu St		Pentium Gold 5405U	2/4	2.3G	2 MB	DDR4-2133	UHD 610		Kensington® MicroS	aver <sup>®'</sup> cable)	<ul> <li>Boot without keyboard and mouse</li> <li>Individual USB port disablement</li> <li>Smart USB protection, allows keyboard/</li> </ul>	
Lote is baced in the second in the indication of the processors with lower memory controller 'System automatically clocks down for the processors with lower memory controller 'System automatically clocks down for the processors with lower memory controller Some: Hard disk password         Administrator password         mouse only, blocks all storage dévices           Storage         Some: Hard Drive / SATA 6.0Gb/s, 2.5"         (Some memory controller Some: Lanovo Calliope Keyboard (USB connector), black         Some: Lenovo Calliope Keyboard (USB connector), black         Some: Lenovo Calliope Keyboard (USB connector), black           Some: M. 2 SSD (2242) / PCIc NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIe NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIe NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIe NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIe NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIe NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIe NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIe NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIE NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIE NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIE NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIE NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIE NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIE NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIE NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2242) / PCIE NNMe, PCIe 3.0 × 4, 32Gb/s Some: M. 2 SSD (2300 / PC) (SOME (200 / PCIE AND A, 200 / PCIE AND A, 2		Core i3-8145U	2/4	2.1G / 3.9G	4 MB	DDR4-2400	UHD 620					
Memory       16GB max, DDR4-2666*, one 260-pin SO-DIMM sockets, non-ECC       • Hard disk password       • Hard disk password         Storage       Some: Hard Drive / SATA 6.0Gb/s, 2.5*, 540 (pm or 7200 pm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5*, 540 (pm or 7200 pm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5*, 540 (pm or 7200 pm Some: Some: M.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: N.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2421) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2421) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2421) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2421) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2421) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2421) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: A.2 SSD (2421) / PCIE NVMe, PCIE 3.0 x 4, 32Gb/s Some: A.2 SSD (2421) / PCIE NVME, PCIE 3.0 X 4, 32Gb/s Some: A.2 SSD (2421) / PCIE NVME, PCIE 3.0 X 4, 32Gb/s Some: A.2 SSD (2421) / PCIE NVME, PCIE 3.0 X 4, 32Gb/s Some: A.2 SSD (2421) / PCIE NVME, PCIE 3.0 X 4, 32Gb/s Some: A.2 SSD (2421) / PCIE NVME, PCIE 3.0 X 4, 32Gb/s Some: A.2 SSD (2421) / PCIE NVME, PCIE 3.0 X 4, 32Gb/s Some: A.2 SSD (2421) / PCIE NVME, PCIE 3.0 X 4, 32Gb/s Some		Core i5-8265U	4/8	1.6G / 3.9G	6 MB	DDR4-2400	UHD 620					
Storage Some:         Some:         Land Drive / SATA 6, OGbys, 2.5°, S400 rpm or 7200 rpm Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2280) / PCIE NVME, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2280) / PCIE NVME, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2280) / PCIE NVME, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2280) / PCIE NVME, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2080) / PCIE NVME, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2080) / PCIE NVME, PCIe 3.0 x 4, 32Gb/s Some: M1 CB SSD (2080) / PCIE NVME, PCIE NS NUB // PCIE NS	Memory	16GB max, DDR4-26 * System automatical	66*, one 2 lv clocks (	260-pin SO-DIMI	M socke	ts, non-ECC with lower memo	orv controlle	Keyboard	Hard disk password			
Some:         Soid State Drive (SSD) / SATA 6 0Gb/s 2.5"         Max           Some:         M2 SSD (2280) / FCle NVMe, PCle 3.0 x 4, 326/s Some: M.2 SSD (2242) / PCle NVMe, PCle 3.0 x 2, 16Gb/s         Tiny (1L), black color; metal case         Optional dust filter           Onooard SATA         One onboard SATA 6.0Gb/s connector         DisplayPort <sup>III</sup> , one NDML, up to 2 independent displays; Max resolution: 4096 FOH2, 4096 FOH	Storage	Some: Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: M.2 SSD (2280) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: M.2 SSD (2242) / PCIe NVMe, PCIe 3.0 x 2, 16Gb/s						Mouse				
Chaphies       Internet modular phases internet methy, bitect 12, one bisplayPort*, one HDMi, up to 2 independent displays; max resolution: 4096x2304 (DP) @ 60Hz; 4096x2304 (HDMI)@ 24Hz       Tiny only       7.0° X 7.2" X 1.4" (1.5" with rubber feet)       2.91 ib (1.32 kg), vary by config         Monitor cable       Optional DP to VGA dongle or DP to HDMI 1.4 dongle       VESA mount       Tiny only       7.0° X 7.2" X 1.4" (1.5" with rubber feet)       2.91 ib (1.32 kg), vary by config         Chipset       Intel Soc (System on Chip) platform       Font ports* (Std.) One USB 3.1 Gen1, one USB 3.1 Type-C Gen 1, one microphone (3.5mm), one headphone / microphone combo jack (3.5mm)       Four ports* (Std.) None       VESA mount       Power supply       Some: 1-year, depot service / service upgrades available       2.91 ib (1.32 kg), vary by config         Audio support       Realtek ALC233VB / internal speaker (1.5 watt)       Power supply       Some: 1-year, depot service / service upgrades available       Some: 1-year, limited onsite service / service upgrades available         VLAN       Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1       Some: Sluetooth 4.2 combo adapter, 2x2       Preloaded operating system         Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2       Environment       ENERGY STAF® 8.0, EPEAT™ Silver rating, ErP Lot 3, TCO, RoHS-compliant, WEEE, REACH         Bluetooth       Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 365, Wi-Fi + Bluetooth 4.2 combo	U U							Optional dust filter				
DisplayPort <sup>m2</sup> , one HDMI, up to 2 independent displays; Max resolution: 4096x2304 (ID) @ 60Hz; 4096x2304 (HDMI) @ 24Hz Optional DP to VGA dongte or DP to HDMI 1.4 dongle       Tiny only       7.0" X 7.2" X 1.4" (1.5" with rubber feet) 179mm X 183mm X 34.5mm (37mm with rubber feet)       2.91 lb (1.32 kg), vary by config         Chipset       Intel SoC (System on Chip) platform       Foor Stand       Optional DP to VGA dongte or DP to HDMI 1.4 dongle       VESA mount Floor Stand       Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation       2.91 lb (1.32 kg), vary by config         Rear ports* (Std.) One USB 3.1 Gen1, one USB 2.1 Type-C Gen 1, one microphone (3.5mm), one headphone / microphone combo jack (3.5mm)       Power supply       Some: 65 watts adapter, autosensing, 88% PSU       Imited warranty       Power supply       Some: 1-year, depot service / service upgrades available       Power supply       Some: 1-year, limited onsite service / service upgrades available       Preloaded operating system         Audio support       Realtek ALC233VB / internal speaker (1.5 watt)       Preloaded operating system       Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1       Preloaded operating system       Some: Windows 10 Pro 64-bit       Some: Windows 10 Pro 64-bit       Some: Windows 10 Home 64-bit       Preloaded applications (only some listed)       Environment       ENERGY STAR* 8.0, EPEAT <sup>TM</sup> Silver rating, ErP Lot 3, TCO, RoHS-compliant, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2       Some: Bluetooth 4.2 combo adapter, 2x2	Graphics	Intel HD Graphics 610/620 in processor, uses main memory. DirectX <sup>®</sup> 12. one								Dimensi	ons (WxDxH)	Weight (Approx.)
Chipset       Intel SoC (System on Chip) platform       Floor Stand       Optional VESA mount bracket kit, supports VESA 75mm and 100mm         Front ports* (Std.) One USB 3.1 Gen1, one USB 3.1 Gen1, one USB 3.1 Gen1, two USB 2.0, one ethernet (RJ-45), one DisplayPort, one HDM       Floor Stand       Optional VESA mount bracket kit, supports VESA 75mm and 100mm         Rear ports* (Std.) Two USB 3.1 Gen1, two USB 2.0, one ethernet (RJ-45), one DisplayPort, one HDM       Power supply       Some: 65 watts adapter, autosensing, 88% PSU         Audio support       Realtek ALC233VB / internal speaker (1.5 watt)       Power supply       Some: 1-year, depot service / service upgrades available         WLAN       Some: 11ac wireless, M.2 Card, Realtek RTL88210CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1       Preloade doperating system         Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2       Nin-Fi + Bluetooth 4.2 combo adapter, 2x2         Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2       Bluetooth 4.2 wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 wireless, N.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 wireless, N.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 wireless, N.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 wireless, integrated in Wi-Fi + BT combo adapter, 2x2       Environment       ENERGY STAR® 8.0, EPEAT™ Silver rating, ErP Lot 3, TCO, RoHS-compliant, WEEE, REACH         Bluetooth       Some: 11ac wireless, N.2 Card, Intel Dual		DisplayPort™, one HDMI, up to 2 independent displays; Max resolution: 4096x2304 (DP)@60Hz; 4096x2304 (HDMI)@24Hz							Tiny only	179mm X 183m	m X 34.5mm (37mm 🏾	
Prover supply       Some: 11 control of the control of												
Rear ports* (Std.) Two USB'3.1 Gen1, two USB 2.0, one of thernet (RJ-45), one DisplayPort, one HDMI       Initial construction of the service of	one headphone / microphone combo jack (3.5mm)											
Rear ports* (Opt.) None * Depending on many factors, actual data transfer speed may be lower than theoretical speed       Limited warranty       Some:       1-year, depot service / service upgrades available         Audio support       Realtek ALC233VB / internal speaker (1.5 watt)       Preloaded operating system         WLAN       Some:       11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1       Preloaded operating system         Some:       11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2       Preloaded applications (only some listed)         Some:       11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 1x1       Preloaded applications (only some listed)         Some:       11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2       Nuereless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2       Environment       ENERGY STAR® 8.0, EPEAT™ Silver rating, ErP Lot 3, TCO, RoHS-compliant, WEEE, REACH         Bluetooth       Some:       Some:       MIL-SPEC test       MIL-SPEC test       MIL-SPEC test								y Some: 1-year, depot service / service upgrades available				
Addio support       Intented speaker (1.5 watt)         WLAN       Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1         Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2       • Lenovo Vantage         Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 1x1       • Lenovo Vantage         Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2       • LinkedIn         Bluetooth       Some: Bluetooth 4.2 wireless, integrated in Wi-Fi + BT combo adapter       Environment         Ethernet       Gigabit ethernet, Realtek RTL8111HN-CG       Environment         Ethernet (Opt.)       None       MIL-STD-810G (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar	Rear ports* (Opt.) None											Limited warranty
Wi-Fi + Bluetooth 4.2 combo adapter, 1x1         Some:       11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2         Some:       11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 1x1         Some:       11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2         Bluetooth       Some:         Some:       11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2         Bluetooth       Some:         Bluetooth       <	Audio support	Realtek ALC233VB / internal speaker (1.5 watt)						Preload	Some: Windows <sup>®</sup> 10 Pro 64-bit Some: Windows 10 Home 64-bit Preloaded applications (only some listed) • Lenovo Vantage • Microsoft Office preloaded;			
Wi-Fi + Bluetooth 4.2 combo adapter, 1x1       Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, wi-Fi + Bluetooth 4.2 combo adapter, 2x2       Linkedin         Bluetooth       Some: Bluetooth 4.2 wireless, integrated in Wi-Fi + BT combo adapter, 2x2       Environment       ENERGY STAR® 8.0, EPEAT™ Silver rating, ErP Lot 3, TCO, RoHS-compliant, WEEE, REACH         Bluetooth       Gigabit ethernet, Realtek RTL8111HN-CG       MIL-SPEC test       MIL-STD-810G (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar	WLAN	Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: Bluetooth 4.2 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Realtek RTL8111HN-CG None None						-				
Wi-Fi + Bluetooth 4.2 combo adapter, 2x2EnvironmentENERGY STAR® 8.0, EPEAT™ Silver rating, ErP Lot 3, TCO, RoHS-compliant, WEEE, REACHBluetooth Ethernet Ethernet (Opt.)Some: Bluetooth 4.2 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Realtek RTL8111HN-CGMIL-SPEC testMIL-STD-810G (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar									• LinkedIn			
Ethernet (Opt.) None Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar								Environment	ENERGY STAR <sup>®</sup> 8.0, EPEAT <sup>™</sup> Silver rating, ErP Lot 3, TCO, RoHS-compliant, WEEE, REACH			
indiadoability indiadoability indiadoability	Ethernet (Opt.)							MIL-SPEC test	Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar			
	Manageability							Accessories	For compatible accessories, please go to http://smartfind.lenovo.com			

Note: The specifications above may not be available in all regions.

Lenovo, October 2020

## ThinkCentre M630e Tiny











(intel)





(intel) inside