

# APC Back-UPS® RS 1200/1500

## High performance battery backup and protection for office computers

The Back-UPS RS provides you with abundant battery backup power, allowing you to work through medium and extended length power outages – *up to 131 minutes!* It also safeguards your equipment from damaging surges and spikes that travel along utility and phone lines. The Back-UPS RS 1200 and 1500 also feature “boost” automatic voltage regulation (AVR), which instantly adjusts low voltages to safe levels, so you can work indefinitely during undervoltage situations. Additional standard features make the Back-UPS RS the perfect unit to protect your business' productivity from the constant threat of power problems and lost data.

## Product Features:



- 1 LCD (Liquid Crystal Display) provides easy to read information about battery and utility conditions.
- 2 “Boost” Automatic Voltage Regulation corrects undervoltages without draining the battery, saving battery power for when you need it most – outages.
- 3 6 “Battery Backup & Surge Protection” outlets keep CPU, monitor and other critical devices running when the power goes out.
- 4 2 “Surge Only” outlets protect printers, fax machines or other equipment without reducing battery capacity.
- 5 Data line surge protection guards against power surges and spikes traveling on phone lines.
- 6 Push button circuit breaker enables quick recovery from overloads.
- 7 3 yr warranty for European Union countries - 2 years elsewhere, Equipment Protection Policy where applicable (200,000 AUD, 150,000 Euros, 75,000 GBP), free technical phone and online support.
- 8 Automatic Diagnostic Testing ensures your unit is ready when you need it.
- 9 Auto shutdown software allows management of the Back-UPS from your computer via USB or serial connectivity:
  - Gracefully shuts down system when battery is low
  - Records utility power and battery conditions
  - Allows for customized set up



## Back-UPS RS 1200 & 1500 LCD Specifications

Model Number	BR1200LCDI	BR1500LCDI
<b>Output</b>		
Output Capacity	1200 VA / 720 Watts	1500 VA / 865 Watts
Output Voltage / Freq. (On utility)	230V / 50/60Hz	230V / 50/60Hz
Output Voltage / Freq. (On battery)	230V / 50/60Hz	230V / 50/60Hz
Output Connections	8 total IEC 320 C13 outlets: 6 battery backup & surge 2 surge protection only	8 total IEC 320 C13 outlets: 6 battery backup & surge 2 surge protection only
Waveform Type	Stepped Approximation to Sine Wave	Stepped Approximation to Sine Wave
<b>Input</b>		
Input Voltage / Frequency	230V / 50/60 Hz	230V / 50/60 Hz
Input Connection	Two detachable 6 ft cords (IEC 320 C13 to IEC 320 C14)	Two detachable 6 ft cords (IEC 320 C13 to IEC 320 C14)
<b>Surge Protection</b>		
AC Power Surge Protection	All outlets	All outlets
Data Line Surge Protection	Analog phone line, RJ-11 (single, 2-wire). For phone, fax, modem, DSL	Analog phone line, RJ-11 (single, 2-wire). For phone, fax, modem, DSL
<b>Physical</b>		
Unit Dimensions (H x W x D)	8.75" x 5.25" x 14.0"	8.75" x 5.25" x 14.0"
Unit Weight	29.7 lbs	30.7 lbs
Shipping Dimensions (H x W x D)	12.0" x 9.75" x 18.0"	12.0" x 9.75" x 18.0"
Shipping Weight	32.7 lbs	34.2 lbs
Color	Black	Black
UPC Code	731304257264	731304257288
<b>Battery</b>		
Battery Type	Maintenance-free, sealed lead-acid battery, leakproof	Maintenance-free, sealed lead-acid battery, leakproof
<b>Management</b>		
Alarms	Visual (LCD) and audible alarms	Visual (LCD) and audible alarms
Auto-Shutdown Software	PowerChute Personal Edition (with USB & serial communications)	PowerChute Personal Edition (with USB & serial communications)
<b>Safety</b>		
Certification/Approvals	BSI 1363, C-Tick, CE, GOST, NEMKO, TUV	BSI 1363, C-Tick, CE, GOST, NEMKO, TUV

APC by Schneider Electric  
132 Fairgrounds Rd  
West Kingston, RI 02892  
USA  
www.apc.com

