msi°

GeForce RTX™ 4080 16GB VENTUS 3X OC







SPECIFICATIONS

| Model Name | GeForce RTX™ 4080 16GB VENTUS 3X OC |
|---------------------------------|--|
| Graphics Processing Unit | NVIDIA® GeForce RTX™ 4080 16GB |
| Interface | PCI Express [®] Gen 4 |
| Core Clocks | Extreme Performance: 2550 MHz (MSI Center) Boost: 2535 MHz |
| CUDA® CORES | 9728 Units |
| Memory Speed | 22.4 Gbps |
| Memory | 16GB GDDR6X |
| Memory Bus | 256-bit |
| Output | DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI 2.1a) |
| HDCP Support | Υ |
| Power consumption | 320W |
| Power connectors | 16pin x 1 |
| Recommended PSU | 750W |
| Card Dimension (mm) | 322 x 136 x 63mm |
| Weight (Card / Package) | 1595g / 2200g |
| DirectX Version Support | 12 Ultimate |
| OpenGL Version Support | 4.6 |
| Maximum Displays | 4 |
| G-SYNC® technology | Y |
| Digital Maximum Resolution | 7680 x 4320 |

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 4.0

A masterpiece of teamwork, fan blades work in pairs to create unprecedented levels of focused air pressure.



Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



Airflow Control

Don't sweat it, Airflow Control guides the air to exactly where it needs to be for maximum cooling.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Copper Baseplate

A solid nickel-plated copper baseplate transfers heat from the GPU to all heat pipes for better cooling.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.

CONNECTIONS



- 1. DisplayPort
- 2. HDMI