



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5070 12G VENTUS 3X OC
Memory	12GB GDDR7
Motor de gráficos	NVIDIA® GeForce RTX™ 5070
Norma Bus	PCI Express® Gen 5
Interfaz de Memoria	192-bit
Velocidad clock núcleo (MHz)	Extreme Performance: 2557 MHz (MSI Center) Boost: 2542 MHz
Velocidad clock memoria (MHz)	28 Gbps
Máximo de pantallas	4
Tecnología G-SYNC™	Y
Salida	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
Soporte HDCP	Y
Consumo (W)	250 W
Alimentación recomendada (W)	650W
Resolución máxima digital	7680 x 4320
Conectores de alimentación	16-pin x1
Soporte DirectX Versión	12 Ultimate
Soporte OpenGL Versión	4.6
Dimensiones (mm)	302 x 121 x 49 mm

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Triple Fan

Three fans and a huge heatsink ensure a cool and quiet experience for you.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Nickel-plated Copper Baseplate

Heat from the GPU and memory is swiftly captured by a nickel-plated copper baseplate and transferred.




Core Pipes

Core Pipes feature a square design to maximize contact with the GPU baseplate for optimal thermal management.



Metal Backplate

A sturdy metal backplate strengthens the graphics card while the airflow vent design reduces excess heat.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.