



Hyper TX3 EVO (EU Version)

Features

- 3 direct contact heat pipes with a base that is engineered to minimize CPU contact gaps – providing excellent heat conduction.
- Option for adding 2nd fan with quick-snap fan brackets to increase cooling performance.
- A mere 17 dBA (minimum speed) is accomplished by utilizing a silent 92mm PWM fan with a wide RPM range.
- Versatile all-in-one mounting solution supporting the latest Intel® LGA 1366 / 1155 and AMD FM1 / AM3+.
- Excellent airflow design with compact heat sink dimension.



■ RR-TX3E-22PK-R1

Compatibility

- All Intel® Socket 1366/1156
1155/775 CPU
 - Intel® Core™ i7 Extreme
 - Intel® Core™ i7
 - Intel® Core™ i5
 - Intel® Core™ i3
 - Intel® Core™2 Extreme/Quad/Duo
 - Intel® Pentium®
 - Intel® Celeron®
- All AMD Socket FM1/AM3+/AM3
AM2+ / AM2 CPU
 - AMD FX-Series
 - AMD A-Series
 - AMD Phenom™ II X4 / X3 / X2
 - AMD Phenom™ X4 / X3
 - AMD Athlon™ II X4 / X3 / X2
 - AMD Athlon™ X2
 - AMD Athlon™
 - AMD Sempron™

(For the latest CPU support information, please visit our website.)

Specifications

| | |
|----------------------|---|
| CPU Socket | Intel® Socket LGA1366/1156/1155/775 AMD Socket FM1/AM3+/AM3/AM2+/AM2 |
| Dimensions | 90 x 79 x 136 mm (3.5 x 3.1 x 5.4 inch) |
| Heat Sink Dimensions | 90 x 51 x 136 mm (3.5 x 2.0 x 5.4 inch) |
| Heat Sink Material | 3 Direct Contact Heat Pipes / Aluminum Fins |
| Heat Sink Weight | 306g (0.68 lb) |
| Fan Dimensions | 92 x 92 x 25 mm (3.6 x 3.6 x 1 inch) |
| Fan Speed | 800 - 2200 RPM (PWM) ± 10% |
| Fan Air Flow | 15.7 - 43.1 CFM ± 10% |
| Fan Air Pressure | 0.35 - 2.63 mmH ₂ O ± 10% |
| Fan Life Expectancy | 40,000 hours |
| Noise Level | 17 - 30 dBA |
| Bearing Type | Long Life Sleeve Bearing |
| Connector | 4-Pin |
| Fan Weight | 73g (0.16 lb) |
| Weight | 386g (0.85 lb) |