



The Hyper H410R RGB, a new member of the longstanding Hyper Series, is an affordable, compact and high performance air cooler that its compact heatsink is a great match for small form factor system. The special fin design optimizes air flow toward heat pipes. Its 92mm squared RGB fan features a wide fan speed range and can be fine tuned for maximum airflow and cooling performance or silent operation. Compatible with all RGB certified motherboards.



# HYPER H410R RGB



### Direct Contact Technology

Direct Contact Technology using 4 copper heat pipes delivers exceptional heat dissipation



### Precise Combination of Air Flow and Heatsink

Stacked fin array ensures minimum airflow resistance allowing cooler air into the heatsink.



### Outstanding Performance in a Compact Size

Compact tower cooler, designed to fit in tight builds with height of 136.5mm



### RGB LED Controller

The wired RGB LED Controller allows for customizable colors and effects with just the touch of a button

**Outstanding Performance in a Compact Size - Compact tower cooler, designed to fit in tight builds with height of 136.5mm**

**Direct Contact Technology - 4 heat pipes with Direct Contact Technology effectively provide excellent heat dissipation.**

**Precise Combination of Air Flow and Heatsink -Stacked fin array ensures minimum airflow resistance allowing cooler air into the heatsink.**

**RGB LED Controller - The wired RGB LED Controller allows for customizable colors and effects with just the touch of a button**

## SPECIFICATIONS

Product Name	Hyper H410R RGB	
Product Number	RR-H410-20PC-R1	
Exterior Color	Silver	
CPU Socket	Intel® LGA 1700 / 1200 / 1151 / 1150 / 1155 / 1156 socket	
	AMD® AM5 / AM4 socket	
Dimensions (Lx W x H)	102 x 84.5 x 136 mm ( 4.0 x 3.3 x 5.3 inch)	
Heat Sink Material	4 Heat Pipes / Direct Contact / Aluminum Fins	
Fan		92mm Fan
	Dimensions (L x W x H)	92 x 92 x 25mm (3.6 x 3.6 x 1 inch)
	Profile	RGB
	Quantity (pcs)	1 PC
	Speed	600 ~ 2000 RPM ± 10%
	Airflow (Max)	59 m <sup>3</sup> /h (34.73 CFM)
	Pressure (Max)	1.86 mmH <sub>2</sub> O
	MTTF	>40,000 Hours
	Noise Level (Max)	29.38 dB(A)
	Bearing	Rifle
	Power Connector	4-Pin PWM
	Rated Voltage	12 VDC
	Rated Current	0.19 A
	Safety Current	0.4 A
Power Consumption	2..28 W	
Warranty	2 years	

## PACKING INFORMATION

EAN code	4719512094679
UPC code	884102067099
Net weight	0.5 kg
Gross weight	0.62 kg
Package dimension (L x W X H)	12 x 9.8 x 18.7 cm
Carton dimension (L x W x H)	60 x 38 x 22 cm
Units/CTN	18

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	7128	36	N/A
40'	14256	36	N/A
40 HQ	15840	40	N/A