Version Information	
Product Name	Microsoft [®] SideWinder™ X6 Keyboard
Product Version	Microsoft SideWinder X6 Keyboard v1.0
Keyboard Version	Microsoft SideWinder X6 Keyboard v1.0
Product Dimensions	INICIOSOR SideWilhaer At Reyboard VI.0
Keyboard Length	20.2 inches (513 millimeters)
Keyboard Width	9.22 inches (234 millimeters) includes palm rest
Keyboard Depth/Height	1.80 inches (45.8 millimeters) with tilt legs extended
	46.6 ounces (1320 grams) includes numeric keypad attached
Keyboard Weight Cable Length	78.7 inches (2000 millimeters)
	76.7 inches (2000 minimeters)
Compatibility and Localization	USD Competible
Interface	USB Compatible
Operating Systems	Microsoft Windows® Vista™ and Windows XP
Top-line System Requirements	Microsoft Windows Vista or Windows XP
	• 100 MB hard disk space
	Powered USB port D D :
	• CD Drive
0 (1.7)	Microsoft IntelliType Pro 6.3
Compatibility Logos	Certified for Microsoft Windows Vista
	• USB Certified Logo
Software Localization	Microsoft IntelliType Pro software may be installed in Simplified Chinese, Traditional Chinese, English, French,
	German, Italian, Japanese, Korean, Brazilian Portuguese, Iberian Portuguese, or Spanish. If available, standard setup
	will install the software in the default OS language. Otherwise, the English language version will be installed.
Keyboard Localization	Available language sets will vary by product and sales channel
	104 key configuration: Chinese (Traditional), English (North America), International English (Euro), International
	English (ROW), and Russian
	105 key configuration: Danish, English (UK), Finnish/Swedish, French (Canada), French (France), German, Italian,
	Norwegian, and Spanish (Latin America)
	106 key configuration: Korean
	109 key configuration: Japanese
Product Feature Performance	
Product Feature Performance QWERTY Key Life	20,000,000 actuations per key
	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro
QWERTY Key Life Hot Key Features	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle
QWERTY Key Life Hot Key Features Hot Key Life	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No.	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes Yes
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes • FCC Declaration of Conformity (USA)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes * FCC Declaration of Conformity (USA) • UL and cUL Listed Accessory (USA and Canada)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes Yes • FCC Declaration of Conformity (USA) • UL and cUL Listed Accessory (USA and Canada) • ICES-003 data on file (Canada)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes • FCC Declaration of Conformity (USA) • UL and cUL Listed Accessory (USA and Canada) • ICES-003 data on file (Canada) • TUV-TCertificate (Germany)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes Yes • FCC Declaration of Conformity (USA) • UL and cUL Listed Accessory (USA and Canada) • ICES-003 data on file (Canada) • TUV-TCertificate (Germany) • CE Declaration of Conformity, Safety, and EMC (European Union)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes Yes • FCC Declaration of Conformity (USA) • UL and cUL Listed Accessory (USA and Canada) • ICES-003 data on file (Canada) • TUV-TCertificate (Germany) • CE Declaration of Conformity, Safety, and EMC (European Union) • GOST Certificate (Russia)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes Yes • FCC Declaration of Conformity (USA) • UL and cUL Listed Accessory (USA and Canada) • ICES-003 data on file (Canada) • TUV-TCertificate (Germany) • CE Declaration of Conformity, Safety, and EMC (European Union) • GOST Certificate (Russia) • VCCI Certificate (Russia)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes Yes • FCC Declaration of Conformity (USA) • UL and cUL Listed Accessory (USA and Canada) • ICES-003 data on file (Canada) • TUV-TCertificate (Germany) • CE Declaration of Conformity, Safety, and EMC (European Union) • GOST Certificate (Russia)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes Yes • FCC Declaration of Conformity (USA) • UL and cUL Listed Accessory (USA and Canada) • ICES-003 data on file (Canada) • TUV-TCertificate (Germany) • CE Declaration of Conformity, Safety, and EMC (European Union) • GOST Certificate (Russia) • VCCI Certificate (Russia)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes Yes • FCC Declaration of Conformity (USA) • UL and cUL Listed Accessory (USA and Canada) • ICES-003 data on file (Canada) • TUV-TCertificate (Germany) • CE Declaration of Conformity, Safety, and EMC (European Union) • GOST Certificate (Russia) • VCCI Certificate (Russia) • VCCI Certificate (Japan) • ACMA Declaration of Conformity (Australia)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes Yes -FCC Declaration of Conformity (USA) - UL and cUL Listed Accessory (USA and Canada) - ICES-003 data on file (Canada) - TUV-TCertificate (Germany) - CE Declaration of Conformity, Safety, and EMC (European Union) - GOST Certificate (Russia) - VCCI Certificate (Japan) - ACMA Declaration of Conformity (Australia) - BSMI Certificate (Taiwan)
QWERTY Key Life Hot Key Features Hot Key Life Multi-Media Key Features Multi-Media Key Life Special Features Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Model No. Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Quick Launch, Macro record, Next Game mode, Cruise Control, 6 Programmable Macro keys, Calculator, and Macro Shift Toggle 500,000 actuations per key Play/Pause, Next/Back Track, Mute, Volume Knob 500,000 actuations per key Backlit keyboard, Detachable number pad, Padded palm rest, Numeric Pad with Productivity Mode and Macro Mode for additional programmable keys 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at 0% to 90% relative humidity (non-condensing) 32° F (0° C) to 104° F (40° C) at 0% to 90% relative humidity (non-condensing) 1361 People's Republic of China (PRC) Yes *FCC Declaration of Conformity (USA) *UL and cUL Listed Accessory (USA and Canada) *ICES-003 data on file (Canada) *TUV-TCertificate (Germany) *CE Declaration of Conformity, Safety, and EMC (European Union) *GOST Certificate (Russia) *VCCI Certificate (Russia) *VCCI Certificate (Taiwan) *ACMA Declaration of Conformity (Australia) *BSMI Certificate (Taiwan) *WEEE (European Union)

Results stated herein are based on internal Microsoft testing. Individual results and performance may vary. Any device images shown are not actual size. This document is provided for informational purposes only and is subject to change without notice. Microsoft makes no warranty, express or implied, with this document or the information contained herein. Review any public use or publications of any data herein with your local legal counsel.

©2008 Microsoft Corporation. The names of actual companies and products mentioned herein may be trademarks of their respective owners.